

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS								
REV	DESCRIPTION	DATE	INITIAL	APPROVED				
Α	CH'D -17 BOM INFO, ADDING AN126234.	11/8/2012	RJC	SE				






NOTE: 1. RB T103329-101 SAME AS RB T101509.

## RED BARN MACHINE


ASSY QTY	ASSY QTY	в/О	Part #	UNIT	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.	TOOL SET, MAIN TRAI	18MISSIC	n, backlash
			-3	1	SLEEVE	6061	Ø3 X 3-1/4	2	DWG NO. RB T103	3329-10	)] REV
			-5	1	PLUG	6061	Ø2-3/4 X 1-3/8	3	MAT'L	DRAWN B	Y: CLOUGH
			-7	1	BOLT	4140	1/2-20 X 4-1/8 MCMASTER-CARR #92580A111 (NEEDS MODIFIED)	4	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	APPROVE	D Weil
		B/O	-9	2	HEX NUT	STEEL	1/2-20 UNF MCMASTER-CARR #94895A825	1	.XXX ± .005 FRACTIONS ± 1/32 ANGLES ± .5°	HEAT TREAT FINISH	
		B/O	-11	1	WASHER	STEEL	1/16 X 1/2 ID X 7/8 OD MCMASTER-CARR #95229A550	1	ANGLES ±.5°  1. BREAK ALL SHARP EDGES .015 x 45	enec.	
		B/O	-13	2	WING NUT	STEEL	1/4-28 UNF MCMASTER-CARR #90866A129	1	OR .015R		SED ON MODEL
		B/O	-15	2	FLAT WASHER	STEEL	1/4 ID X 1/2 OD MCMASTER-CARR #95229A430	1	2. DIMENSIONAL LIMITS APPLY AFTER PLATING BELL 206L4, 40		L 206L4, 407
		B/O	-17	2	THREADED STUD	STEEL	1/4-28 UNF X 1-1/2 #AN126234	1	SCALE 1:2 DATE 9	/5/2012	SHEET 1 OF 4




This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.

REVISIONS

REV DESCRIPTION DATE INITIAL APPROVED



SECTION B-B



NOTE; 1. RB T103329-101-5 SAME AS RB T101509-5.


## RED BARN MACHINE TOOL SET, MAIN TRANSMISSION, BACKLASH DWG NO. REV RB T103329-101-5 DRAWN BY: CLOUGH MAT'L 6061 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/32 XX ± .01 ANGLES ± .5° .X ± .1 APPROVED CLEAR ANODIZE SPEC MIL-A-8625F, TYPE II, CLASS D. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING USED ON MODEL BELL 206L4, 407 SCALE DATE 9/5/2012 SHEET 3 OF 4


(-5)

**PLUG** 

This drawing, specifications, and concepts contained here in are the sole property of Red Barn Machine, and may not be reproduced or used in any fashion without the prior written permission of Red Barn Machine.


	REVISIONS							
REV	DESCRIPTION	DATE	INITIAL	APPROVED				
Α	CH'D -17 BOM INFO. ADDING AN126234.	11/8/2012	RJC	SE				







NOTE: 1. RB T103329-101-7 SAME AS RB T101509-7.



**BOLT**